

GENERAL DISK SPECIFICATIONS FOR TROYK PRINTING CORPORATION

Files should normally be built at ¼ the size of the final trim size for each printed piece. However, some projects are preferred at ½ size – **please discuss specifics with your sales person or project coordinator for each project to ensure accuracy.**

All files must be accompanied by color proof of the final file. Matchprints, Kodak Approvals or other similar contract proofs are requested.

Please include a file directory with each disk and highlight the files we are to use. All screen and printer fonts should be included on the disk with any other supporting files for each project.

All photographs and other images should be scanned at 300 dpi at file size.

All text and line art should be scanned at 800-1000 dpi at file size.

Any low-res images in your files requiring replacement should be marked as FPO on your supplied proof.

Finished document set up should be done in Quark Xpress for Macintosh whenever possible.

Supporting files, including colors you have created and gradations work best if created in Adobe Illustrator or Aldus Freehand for Macintosh. All silhouettes must have clipping paths that are clean and precise.

Although we can accept files via Internet or in a PC format the best quality reproduction is produced from a Macintosh computer. Additional charges will be incurred for conversion of PC or PDF files.

All cost estimates supplied are based on film output directly from your disk. Any alterations required will be an additional cost.

Please call us as soon as you begin preparing your files with any questions about our specifications and we will be happy to discuss and clarify. Our goal is to help ensure your printing schedules and posting dates are met.

TROYK PRINTING CORPORATION
9980 S. Oakwood Park Dr., Franklin, WI 53132
PHONE 414-423-2000 or 800-880-1864
FAX 414-423-2211
sales@troyk.com